



A versatile dedicated sweeper collector unit with hydraulic dumping hopper. The TCX combines robust construction with sheer sweeping power. The unit requires two hydraulic services for operation. Service one is connected to the high torque drive motor whilst service two connects to the hopper ram and allows for convenient dumping of the internal hopper from the tractor seat. The powerful direct drive motor is fitted with relief valve protection whilst the reversible hitch frame allows for front or rear '3 point linkage' mounting. Large diameter heavy duty castor wheels cope with the arduous terrain whilst the quick change brush design reduces servicing time and cost. The unit has integrated parking stands for storage and servicing when not in use.



Model	Mount	Sweeping width	Width	Depth	Height
TCX-240	Front/Rear	2.29m	2.63m	1.74m	0.91m

Specification

- Use: Heavy – Extra heavy duty sweeping with collection.
- Mounting: Tractor front or rear '3 point linkage' CAT 2.
- Hyd Serv 1 (Drive): 40–70 litre/min flow rate @ min 140 BAR.
- Hyd Serv 2 (Hopper): Reversible service @ 140 BAR.
- Brush Adjust: Threaded Vertical sliders.
- Brush Spec: 560mm diameter: poly, or poly/wire mix.
- Hopper: 240 litre capacity - hydraulic dump.
- Castors: 250mm Diameter. Heavy duty.
- Drive: Reversible high torque motor - relief valve protection.

